



Stainless Steel Multi-Bucket System

Stainless steel cart with two buckets and downpress wringer

Description

This lightweight, stainless steel, and easy to maneuver multi-bucket system offers maximum flexibility and can be used with two or three 7-gallon (27L) buckets depending upon in-house protocols. An extendable frame pulls out of the front of the fully autoclavable cart to accommodate an additional bucket, part number 2617. The cart features non-marring run quiet wheels. The removable handle makes it convenient for autoclaving and storage. A lip around the top edge of the buckets allows for easy lifting. Includes 2 buckets and heavy-duty stainless steel downpress wringer that is compatible with all sizes of VertiKlean®, VertiKlean® MAX™, QuickTask™, and Edgeless® Mops. Autoclavable at 121°C for 30 minutes.

Technical Information	
Materials of Construction	
Cart	Stainless steel, Type 304
Wringer	Stainless steel, Type 304, downpress
Casters	Stainless steel frames with blue Kryptonite™ autoclavable wheels
Buckets	Stainless Steel, Type 304, deep drawn
Finish	Electropolished
Dimensions	
Cart Dimensions	L x W x H, (in / cm) 26 x 24 x 36 / 66 x 60 x 92
Additional information	
2710 replacement wringer 2617 bucket, 7 gallon (27L) 2647 replacement front casters 2648 replacement back casters 2649 replacement wheels	

Cart 2700

Notes:

- 1) Data shown are typical values and should not be used as product specifications.
- 2) The information presented here is applicable to the part numbers shown above, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

Revision date: 04/29/16



Copyright © 2016 Contec, Inc. All rights reserved.

North America
P.O. Box 530
Spartanburg, SC 29304 USA
Phone: +1-864-503-8333
www.contecinc.com

Europe
Zl du Prat – RP 3707
56037 VANNES Cedex
FRANCE
+33 297 437 690

China
No.17 Longyun Road
Suzhou 215024
CHINA
+ 86-512-6274 4050