QuickTask[®] Mop, TASK0200

The QuickTask[™] range consists of a variety of flat mop heads that can be easily attached to a choice of flat mop head frame and handle assemblies.

QuickTask TASK0200 and TASK0250 mop heads are constructed from multilayers of 100% knitted polyester creating a highly sorbent mop which allows for an even application of solution. The cleanroom laundered polyester ensures a very low level of particulates making the mop suitable for use in the highest grade of cleanroom.



Features	Benefits
Cleanroom laundered	• 100% polyester knit ensures a low level of particulates
Sorbent multilayer knitted surface	 Applies solutions evenly Suitable for removal of light soils, residues and biofilms
Available gamma irradiated and validated sterile to a Sterility Assurance Level of 10-6	Suitable for all grades of pharmaceutical cleanrooms
Lightweight and ergonomic	• The lightest mop cover in the range allows for ergonomic use and efficient surface contact

Part No.	Description	Packaging
TASK0200	QuickTask Polyester Knitted Mop Head, 16" x 5" (41x13cm)	4 mop/bag; 12 bags/case
TASK0250	QuickTask Polyester Knitted Mop Head, 16" x 5" (41x13cm), sterile 1 mop/bag; 40 bags/v	
2740	QuickTask Polypropylene Mop Frame, 16" x 4.25" (41x11cm) 1 each/case Compatible with handle 2725E with adapter 2758	
2749	QuickTask Stainless Steel Mop Frame, 15.5" x 3.75" (40x10cm)	1 each/case

PDSM009 010621

Contec, Inc Spartanburg, SC United States Tel: +1 (864) 503-8333 Contec Vannes Cedex France Tel: +33(0) 2 97 43 76 98 Contec Cleanroom Technology (Suzhou) Co. Ltd Suzhou China Tel: +86-512-6274 4050 Copyright © 2021 Contec, Inc. All rights reserved.



Product Information

Mop materials	100% knitted polyester fabric	
Mop construction	Multilayer sewn lamination/sealed border	
Chemical compatibility	Compatible with a wide range of chemicals and disinfectants (bleach safe/quat safe)	
Dimensions; inches (cm)* As Packaged; nominal: Mounted on frame:	15.5" x 5.25" (39.4x13.3cm) 16" x 4.5" (41x11.5cm)	
Environment	ISO 4-8 Grade A/B for sterile, C/D for nonsterile	
Compatible mop frames	2749 (stainless steel) and 2740 (autoclavable polypropylene).	
Sterile	Available validated sterile	
Shelf life	Sterile: 2 years from manufacturing date	



Technical Data

Attribute (units)	Typical Value	Test Method
Mop weight, dry; (g)	74	CTM004-03
Sorbent capacity; (mL/mop)	328	CTM005
Particles $\geq 0.5 \mu m$; (x10 ⁶ /mop)	2.1	CTM006-01
Fibers \geq 100µm; (x10 ³ /mop)	0.08	CTM006-01
Mop Coverage ft ² (m ²)		CTM037-01
S-Curve	262 (24)	
Place and Pull	121 (11)	

Packaging

	EA/OB1	OB1/OB2	OB2/CS	EA/CS	
TASK0200	4	1	12	48	
	EA/OB1	OB1/OB2	OB2/OB3	OB3/CS	EA/CS
TASK0250	1	1	4	10	40

EA = Each, OB1 = Outer Bag 1, OB2 = Outer Bag 2, OB3 = Outer Bag 3, CS = Case

Notes

a) The data shown are typical values and should not be used as product specifications.
b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.
d) CTM – Refers to Contec Test Method
e) Mop Coverage data is based on mop head applying solution such that the mopped surface is visibly wetted across the full mop path with no dry streaking observed, under controlled conditions.
lt is the responsibility of the user to determine appropriate coverage to ensure surfaces are visibly wet for the contact time required for their specific solution.

Contec, Inc Contec Spartanburg, SC Vannes Cede; United States France Tel: +1 (864) 503-8333 Tel: +33(0) 2 9	China	u) Co. Ltd www.contecinc.com
--	-------	---------------------------------