


# Stainless Steel Downpress Wringer

## Heavy-duty wringer for string and flat mops

### Description

The 2710 Wringer is used to very effectively wring solutions from all Contec string and flat style mops. The 2710 wringer provides uniform pressure across the entire flat mop head for complete removal of cleaning solutions and is compatible with Contec cart/bucket systems 2757 and 2650. Made from 100% stainless steel components for excellent durability and cleanliness. For use with Contec cart/bucket systems. May be sterilized by autoclave or gamma irradiation. Autoclavable at 121 degrees Celsius for up to 30 minutes. Compatible with all common disinfectant solutions and most common solvents. For use with Edgeless, VertiKlean, VertiKlean MAX, and QuickTask Mops.

| Technical Information | |
|---|---|
| **Materials of Construction** | |
| Wringer, downpress | Stainless steel, Type 304 |
| Finish | Electropolished |
| | |
| **Outside Dimensions** | **L x W x H, (in / cm)** |
| Wringer, base structure | 19x9.5x18 / 48x24x46 |
| Wringer, handle | 17.5x1 dia. / 44x2.5 dia. |
| | |
| **Additional information** | |
| Autoclavability | Autoclavable @ 121° C for 30 minutes |
| Accessory for 2710 | 2711; type 304 stainless steel mounts to the front of 2710 to hold handles. Mounting hardware included. |



Wringer 2710



2711

Notes:

1) Data shown are typical values and should not be used as product specifications.
2) The information presented here is applicable to the part numbers shown above, as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.

Revision date: 03/30/16

Copyright © 2016 Contec, Inc. All rights reserved.

**North America**
P.O. Box 530
Spartanburg, SC 29304 USA
Phone: +1-864-503-8333
www.contecinc.com

**Europe**
Zl du Prat – RP 3707
56037 VANNES Cedex
FRANCE
+33 297 437 690

**China**
No.17 Longyun Road
Suzhou 215024
CHINA
+ 86-512-6274 4050